



## Electric Series Scissor Lifts

# 1330SE

Compliance with ANSI/CSA standards

### Product Highlights

- Platform capacity up to 240kg(529lbs)
- Easily passes through standard doors and can access elevators
- Exclusive open chassis reduces daily maintenance time
- DC motor drive, giving a longer runtime

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Full-stroke operation
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tires	■ Tilt protection	
■ Integrated hand shield	■ Automatic pothole guard	
	■ Overload sensing system	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

Model	1330SE	
<b>Dimension</b>		
Max Working Height	5.8m(19')	
A Max Platform Height	3.8m(12'6")	
B Max Horizontal Extension	0.6m(23.6")	
C Length-Stowed	1.42m(4'8")	
D Width-Stowed	0.76m(2'6")	
Height - stowed	Rail Folded	1.67m(6'5")
	E Rail Unfolded	1.97m(6'6")
	Fixed Rail	1.97m(6'6")
F Wheelbase	1.11m(3'8")	
Ground Clearance(Pothole Guard Stowed)	0.065m(2.5")	
Ground Clearance(Pothole Guard Deployed)	0.02m(0.75")	
Platform Dimensions(L×W×H)	1.34m×0.7m×1.1m(4'4"×2'3"×3'6")	
<b>Performance</b>		
Platform Allowable Occupants(Indoor)	2 person	
Platform capacity	240kg(529lbs)	
Lift Extension Capacity	100kg(220lbs)	
Drive Speed-Stowed	4km/h(2.5mph)	
Drive Speed-Raised	0.8km/h(0.5mph)	
Lift Time(Unloaded)	30s-33s	
Descent Time(Unloaded)	25s-30s	
Gradeability	25%	
Turning Radius(Inside/Outside)	0.3m/1.35m(12'/4'5")	
Tilt Rating(From to Back/Side to Side)	3°/1.5°	
Tire Size/Type	230×80mm (9×3")80/solid	
<b>Power</b>		
Batteries	12V×2/115Ah	
Power Source	24V DC	
Drive Mode	Motor, Rear wheel	
Charger Input	100-240V AC	
Charger Output	15A	
Hydraulic System Capacity	5L(1.1gal)	
<b>Weight</b>		
Weight(Indoor)	880kg(1,940lbs)	
Standards Compliance	ANSI/CSA	

