

ENGINE POWERED ROUGH TERRAIN SCISSOR LIFTS

3369RD / 4069RD

Compliant with ANSI/CSA standards

PRODUCT HIGHLIGHTS

Outstanding Performance

- Engine-powered rough terrain scissor lift, capable for drivable at full height with 35% gradeability delivering superior performance on sloped and uneven terrain
- Full-time oscillating axle enhances traction and stability for improved off-road capability
- 5'3" (1.6m) wide platform with one-way extension platform

Easy Operation

- One-touch auto-leveling system allows for efficient operation on uneven surfaces, improving productivity and safety

Easy maintenance

- Dual-side out door design and slide-out engine tray design enables quick and convenient maintenance access
- Onboard fault diagnostics with integrated error codes and resolution guidance



Standard Features		
4 WD × 2 WS	Forklift pockets and lifting eyes	Fully proportional controls
Manual storage box	Flashing beacon	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Foldable platform rails	Foam-filled non-marking tires	Auto braking system
Weighing system	Full-time active oscillating axle	Horn and buzzer
AC power to the platform		
Options & Accessories		
Glazier kit	Cold weather heating package	Pipe rack
Telematics		

ENGINE POWERED ROUGH TERRAIN SCISSOR LIFTS

3369RD / 4069RD

Compliant with ANSI/CSA standards

Model	3369RD	4069RD
Dimensions		
Max Working Height	38'9.7" (11.8 m)	46'0.3" (14.0 m)
A Max Platform Height	32'9.7" (10.8 m)	40'0.3" (12.2 m)
B Max Horizontal Reach	4'11.1" (1.5 m)	4'11.1" (1.5 m)
C Length-Stowed (With/Without outriggers)	12'5.6"/10'5.6" (3.8 m/3.19 m)	12'5.6"/10'5.6" (3.8 m/3.19 m)
D Width-Stowed	5'10" (1.78 m)	5'10" (1.78 m)
E Height-Stowed (Rails Folded)	6'4.4" (1.94 m)	6'10.7" (2.1 m)
E Height-Stowed (Rails Unfolded)	8'4.8" (2.56 m)	8'11.5" (2.73 m)
F Wheelbase	7'5.8" (2.28 m)	7'5.8" (2.28 m)
Ground Clearance	8.66" (0.22 m)	8.66" (0.22 m)
Platform Size (L×W×H)	9'2.2"×5'3"×3'7.3" (2.8 m×1.6 m×1.1 m)	9'2.2"×5'3"×3'7.3" (2.8 m×1.6 m×1.1 m)
Performance		
Platform Capacity	992 lbs (450 kg)	805 lbs (365 kg)
Extension Platform Capacity	309 lbs (140 kg)	309 lbs (140 kg)
Max Platform Occupants (Indoor/ Outdoor)	4 Persons/2 Persons	3 Persons/2 Persons
Drive Speed (Stowed)	0~3.5mph (0~5.6 km/h)	0~3.5 mph (0~5.6 km/h)
Drive Speed (Raised)	0~0.3 mph (0~0.48 km/h)	0~0.3 mph (0~0.48km/h)
Lift Time (Unloaded)	42 s~52 s	55 s~65 s
Lower Time (Unloaded)	40 s~50 s	50 s~60 s
Gradeability	35%	35%
Tilt Rating (Front-to-back)	3°	3°
Tilt Rating (Side-to-side, Outriggers Retracted/Deployed)	2°/0.8°	2°/0.8°
Max Outtrigger Levelling (Front-to-back)	5.3° (front) /4.2° (back)	5.3° (front) /4.2° (back)
Max Outtrigger Levelling (Side-to-side)	11.7°	11.7°
Turning Radius (Inside/Outside)	6'11.1"/15'1.1" (2.11 m/4.6 m)	6'11.1"/15'1.1" (2.11 m/4.6 m)
Tire Spec/Type	26×12-16.5/Solid	26×12-16.5/solid
Power		
Drive × Steer	4 WD×2 WS	4 WD×2 WS
Engine	Kubota D1105-E4B-EU-X1	Kubota D1105-E4B-EU-X1
Hydraulic Tank Capacity	19 gal (15.8gal(UK)/72L)	19 gal (15.8gal(UK)/72L)
Fuel Tank Capacity	12.7 gal (10.6 gal (UK)/48L)	12.7 gal (10.6 gal (UK)/48L)
Battery	12 V, 60 Ah	12 V, 60 Ah
System Voltage	12 VDC	12 VDC
Weight		
Weight (With outriggers/Without outriggers)	9,061 lbs (4,110 kg) / 8,046 lbs (3,650 k g)	11,420 lbs (5,180 kg) / 10,406 lbs (4,720 kg)
Standards Compliance		
ANSI/CSA		

